

# CUSTOMER SERVICE BULLETIN

## Radio Shack® CUSTOMER SERVICE BULLETIN

400 Atrium—One Tandy Center, Fort Worth, Texas 76102

Bulletin No.	4503-6
Description	Payroll
Model	Model II
Stock No.	26-4503 Version 1.0
Date	August 11, 1980
Page 1 of	2

### Problem

The Federal unemployment insurance rate factor has been reported to be to the third decimal place. Right now the program will allow the change to only the second decimal place.

### Solution

The problem is corrected by following the steps listed below.

1. Backup the diskette(s) and make the changes on the Backup copy of the program.
2. In BASIC load the program by typing LOAD"CHNGCO".
3. Make the following corrections:

CHANGES (Retype the line or refer to the Edit section of the owners manual)

Old Line: 1620 CLEAR2000:GOSUB400:CLS:PRINTCF\$:PRINT@(2,16),R\$" OTHER RATES AND LIMITS "N\$:DIMFT\$(9),FT(11):F9\$="###,###,##-":F8\$="###"

New Line: 1620 CLEAR2000:GOSUB400:CLS:PRINTCF\$:PRINT@(2,16),R\$" OTHER RATES AND LIMITS "N\$:DIMFT\$(9),FT(11):F9\$="###,###,##-":F8\$="###":F7\$=LEFT\$(F9\$,10)+"#-"

Old Line: 1670 FORI=1TO8:PRINT@(I+6,0),R\$:USING" ## ";I;:PRINTN\$:TAB(10);C6\$(I);:FORK=1TO2:J=VAL(MID\$(C7\$(I),2\*K-1,2)):IFJ>0THENPRINTTAB(K\*13+12);USINGF9\$;FT\$(J);

New Line: 1670 FORI=1TO8:PRINT@(I+6,0),R\$:USING" ## ";I;:PRINTN\$:TAB(10);C6\$(I);:FORK=1TO2:J=VAL(MID\$(C7\$(I),2\*K-1,2)):IFJ>0ANDI=5ANDK=1THENPRINTTAB(K\*13+12);USINGF7\$;FT\$(J);ELSEIFJ>0THENPRINTTAB(K\*13+12);USINGF9\$;FT\$(J);

# CUSTOMER SERVICE BULLETIN

Subject Payroll Bulletin # 4503-6 Page 2 Of 2

Old Line: 1760 PRINT@(19,0),EL\$:PRINT@(19,8),P\$;C6\$(I);" ";;FL=8:GOSUB300:  
IFCF=1ORCF=2THENK=2:NEXT:GOTO1710ELSEIFLEN(IN\$)>0THENFT#(J)=VAL(IN\$):  
PRINT@(I+6,K\*13+12),USINGF9\$;FT#(J);

New Line: 1760 PRINT@(19,0),EL\$:PRINT@(19,8),P\$;C6\$(I);" ";;FL=8:GOSUB300:  
IFCF=1ORCF=2THENK=2:NEXT:GOTO1710ELSEIFLEN(IN\$)>0THENFT#(J)=VAL(IN\$):  
IFI=5ANDK=1THENPRINT@(I+6,K\*13+12),USINGF7\$;FT#(J);ELSE  
PRINT@(I+6,K\*13+12),USINGF9\$;FT#(J);

4. Type SAVE"CHNGCO" to save the changes in the program.
5. At TRSDOS Ready, make a backup copy of the corrected diskette.