

A Perfect **MATE**...

For the **Executive!**

Your choice of
Internal Storage

80C286 - 20 mhz
80386 - 25 mhz



LCD or
Gas Plasma

Executive
Attache
Styling

EXECuMATE® **PORTABLE WORKSTATION**

Exclusive Features

- VGA "Page-White" LCD Display
- Optional VGA Gas Plasma Display
- 50 mb to 200 mb HDD Storage (19 ms)
- Internal 1.44mb or 1.2mb Floppy Drive
- Optional 40mb Removable Hard Disk
- External Rechargeable DC Battery
- Upgradeable CPU
- External Keyboard and Video Ports
- 5 Industry Standard Expansion Slots
- Ruggedized Metal Case, FCC Spec.
- Up to 8 MB 32-Bit (onboard) RAM
- U.S. Designed & Manufactured

U.S. MICRO
Engineering®

Securing America's Micro Futures

Contact your local Computer Dealer!

P.O. Box 17728, Boulder, CO 80308
Sales (303) 939-8700
Fax (303) 939-8791

EXECuMATE[®] PORTABLE WORKSTATION

SPECIFICATIONS

Processor

- Intel 80386 running at 25/20/8 MHZ (SI: 31, 24)
- Harris 80C286 running at 20/16/8 MHZ (SI: 24.0)
- Intel 80387 and 80C287 Math Coprocessor Sockets
- Real Time Clock/Calendar with Battery
- Upgradeable Processor
- Chips & Technology Programmable Chip Set

Memory (RAM)

- 1 Megabyte RAM (Zero-Wait-State)
- Extendable to 8MB RAM on System Board or 16 MB RAM with one expansion card (EMS Compatible)
- 256KB Video Ram, Award Bios

Display

- 10" Page-White LCD (640x480 Res., 80x30 Lines)
- Optional 10.5" Gas Plasma (640x480 Res., 80x30 Lines)
- Four Grey Scales with adjustable contrast
- Upgradeable to Color Panel (256 Colors)
- EGA Emulation (Upgradeable to VGA)

Storage/Disk Drives

- Two Internal Disk Drives (3.5" or 5.25" Size)
- 50 MB Model offer 19 ms AST (1:4 Int.)
- 100 MB & 200 MB Models offer 14ms AST (1:1 Int.)
- HDD On/Off Switch to increase battery life
- Internal 2.88/1.44 MB Floppy Disk Drive (PS/2 Compatible) or Internal 1.2 MB Floppy Disk Drive (AT Compatible)
- 64kb Disk Cache Onboard (12 ms effective seek)

Keyboard

- Full Function 102-Key AT-Style Keyboard with LEDs
- 12 Function Keys and Separate Numeric Keypad & Cursor
- External Keyboard Port (102-Key Enhanced)

Operating Systems/BIOS

- MS-DOS, MS-OS/2, UNIX, XENIX (sold separately)
- 286 Award/AMI Bios, 386 AMI Bios with setup

Dimensions/Weight

- 17.4"w x 15.9"d x 3.9"h, Attache Case Styling
- 17.4 Pounds (with internal 50 MB HDD & FDD)

Interfaces

- FIVE Internal Full Length AT Compatible SLOTS
- External RGB Monitor & Keyboard Port
- 9-pin Serial Comm Port
- 25-pin Parallel Printer Port

Power

- Internal 110v-220v AC, 100-150 watt
- Optional DC Power Pack, (Rechargeable*)
- Designed to meet FCC Specifications

Options

- 2400 & 9600 Baud Modem or Fax Comm. Board
- 40 mb Removable Hard Disk Drive
- 650 mb Optical Disk Drive (CD-ROM, WORM, WMRM)
- External DC Power Pack (Rechargeable*)
- 287 & 387 Math Coprocessors
- Voice Recognition & Synthesis Module
- 60/120mb Streaming Tape Backup
- Expansion Chassis (4 16-Bit AT[®] Slots, 2 Drives)
- Deluxe Leather Carrying Case
- Diconix Portable Printer

Limited Warranty/Design

- One Year Parts and Labor
- U.S. Designed, U.S. Manufactured

MODELS

Model No.	Description
EXEC 286-20	EXECuMATE 286-20 mhz <ul style="list-style-type: none"> • 20/16/8 mhz 80286 CPU, 1 mb RAM • 1.44mb Floppy Drive • 50mb Hard Disk Drive, 19ms AST • 640x480 Page-White LCD, Backlit
EXEC 386-25	EXECuMATE 386-25mhz <ul style="list-style-type: none"> • 25/20/8 80386 CPU, 1 mb RAM • 1.44mb Floppy Drive • 50mb Hard Disk Drive, 19ms AST • 640x480 Page-White LCD, Backlit
EXEC 386-33	EXECuMATE 386-33mhz <ul style="list-style-type: none"> • 33/20/8 mhz 80386 CPU, 2 mb RAM • 1.44mb Floppy Drive • 50mb Hard Disk Drive, 19ms AST • 640x480 Gas Plasma Display

Specifications are subject to change without notice.
 AT, IBM AND PS/2 are registered trademarks of IBM.
 MS-DOS, MS-OS/2 are trademarks of Microsoft.
 Xenix, Unix are trademarks of SCO and AT& T.